



High Flow

Buckeye's High Flow product line of fire extinguishers sets the standard for quality and reliability in the high flow extinguisher category. Designed to deliver outstanding performance, Buckeye High Flow extinguishers are specifically suited to meet the demands of industrial applications where NFPA 10 requires the installation of high flow extinguishers; installations where hazards such as pressurized flammable liquids, pressurized gas, or three dimensional fires exist.

Key Features

- Exceeds UL and NFPA requirement for 1 lb. per second discharge rate
- UL and ULC Listed
- Rugged steel cylinders, plated brass valves, and baked-on polyester epoxy top coat
- Meets DOT and TC requirements
- US Coast Guard Approved with listed marine bracket
- Trilingual labels-English, Spanish, and French
- Widest selection of agents and sizes in the industry
- Operating temperature is -65°F to 120°F
- Operating pressure 195 psi

Third Party Approvals For Peace Of Mind



Model	10 HF ABC	10 HF PK	10 HF STD	13 HF ABC	13 HF PK	13 HF STD	20 HF ABC	20 HF PK	20 HF STD	30 HF ABC	30 HF PK	30 HF STD
Pt. #	11350	11650	11850	11150	11250	11450	12350	12650	12850	13350	13650	13850
Agent Capacity	10 Lbs. (4.54 kg)	10 Lbs. (4.54 kg)	10 Lbs. (4.54 kg)	13.2 lbs. (6 kg)	13.2 lbs. (6 kg)	13.2 lbs. (6 kg)	20 lbs. (9.07 kg)	20 lbs. (9.07 kg)	20 lbs. (9.07 kg)	30 lbs. (13.6 kg)	30 lbs. (13.6 kg)	30 lbs. (13.6 kg)
UL/ULC Rating	1-A:20-B:C	20-B:C	10-B:C	1-A:20-B:C	20-B:C	10-B:C	4-A:60-B:C	60-B:C	60-B:C	4-A:80-B:C	80-B:C	60-B:C
Discharge Rate (lb/sec)	1.11	1.03	1.17	1.26	1.11	1.25	1.17	1.57	1.34	1.43	1.56	1.75
Discharge Time (Secs)	10 sec	10	9	11	12	10	18	13	14	22	21	17
Discharge Range ft (m)	30-40 ft (9.14-12.19m)	30-40 ft (9.14-12.19m)	30-40 ft (9.14-12.19m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)
USCG Approval	Type A Size II Type B:C Size II	Type B:C Size II	Type B:C Size II	Type A Size II Type B:C Size II	Type B:C Size II	Type B:C Size II	Type A Size II Type B:C Size III	Type B:C Size III	Type B:C Size III	Type A Size II Type B:C Size IV	Type B:C Size IV	Type B:C Size IV
Ship Weight*	19	19	19	25	25	25	35	35	35	48.5	48.5	48.5
Unit Height (in.)	16.75	16.75	16.75	17.5	17.5	17.5	21.25	21.25	21.25	27.5	27.5	27.5
Unit Width (in.)	8.25	8.25	8.25	8.25	8.25	8.25	8.75	8.75	8.75	8.75	8.75	8.75
Unit Diameter (in.)	6	6	6	7	7	7	7.5	7.5	7.5	7.5	7.5	7.5

*Ship Weight is an approximate weight used for calculating shipping costs. Actual unit weight is printed on the product label.