



Wheeled Halotron

Our Wheeled Halotron units are designed to deliver exceptional performance whatever the environment. DOT/TC approved cylinders, rugged frames and semi-pneumatic tires are key features of these UL/ULC approved extinguishers. Tow Loops can be added upon request.

Halotron is a residue-free, non-conductive agent that is suitable for use on Class A, Class B and Class C fires.

Typical Uses: For protecting sensitive electronic equipment in research facilities, vehicle/aircraft/marine service centers, and flight lines.



Third Party Approvals For Peace Of Mind



Model	W-65	W-150
Description	65 lb. Stored Pressure	150 lb. Stored Pressure
Part #	76500	71500
Agent Capacity	65 lb. (29.5 kg)	150 lb. (68 kg)
UL/ULC Rating	4A:60B:C	10A:120B:C
Discharge Time	20 sec	30 sec
Operating Temperature Range	-40° to 120°F (-40° to 49°C)	-40° to 120°F (-40° to 49°C)
Operating Pressure	150 psi (1035 kPa)	150 psi (1035 kPa)
Range	15-25 ft. (4.6-7.6 m)	23-36 ft. (7-10.7 m)
Unit Weight*	252 lb. (114 kg)	396 lb. (180 kg)
Unit Height x Width x Depth	50" x 24" x 41.5" (127 x 61 x 105 cm)	62" x 24" x 41.5" (157.5 x 61 x 105 cm)
Hose Diameter & Length	.75 in x 25 ft. (1.9 cm x 7.6 m)	.75" x 50 ft. (1.9 cm x 15.2 m)

* For information purposes. Unit weight ranges are printed on the product label.

